

Product Features

- Sleek and compact appliance style design
- Designed for mineral tanks up to 10" x 35" tall
- Direct access to electronic functions with integrated face plate
- Blow-molded cabinet with injection-molded cover and salt lid
- Brine compartment and valve are easily accessible under cover
- Large salt opening with easily detached snap-fit lid
- Foam baffle protects electronic controls from brine vapors
- Molded features at top and bottom of cabinet hold mineral tank in place
- Integral side handles allow easy installation and positioning
- Space saving footprint

Options

- Designed for 5600 and ProFlo valves with SXT electronics
- Available in contemporary Cool Gray
- Outdoor version for standard mechanical 5600, or 5600SXT and ProFloSXT with blind face plate

Materials

Cabinet material	Polyethylene
Cover material	Polystyrene
Salt lid material	Polystyrene
Control panel material	ABS

Nominal Dimensions

Overall height with cover	44-1/2"	25-1/2"
Brine cabinet height (less cover)	36"	18"
Width	12-1/2"	12-1/2"
Depth	22"	22"

Typical Applications

Water softener tank sizes	6"-10" dia. x 35" tall	6"-10" dia. x 18" tall
---------------------------	------------------------	------------------------

Additional Information

Salt capacity	225 lbs. (approx.) 10" x 35" tank and brine well installed	110 lbs. (approx.) 10" x 16" tank and brine well installed
Estimated shipping weight (not including carton)	18 lbs.	12 lbs.
Temperature	34° - 110° F	34° - 110° F

